



1177 W Maple Rd,  
 Suite 1,  
 Clawson, MI, 48017  
 P:(248)288-0002 F:(248)284-0008  
[www.foamforyou.com](http://www.foamforyou.com)

**CERTIFICATE OF ANALYSIS**

Date Created: 3/24/2020

**Quality Department:**

Listed are the physical Properties of the foam tested to ASTM D3574 Standards, shipped on the following order:

SO#: 1516532-10

Run Number: 8005311

PO#: 02262020

Foam Type: ZS25GY

2S25GY DRY FAST 50 ILD

Characteristics	Results	Specification Limits
Color:	White	
Density:	1.66	1.55-2.20 lbs/ft <sup>3</sup>
Pore Size:	20	15-40 ppi
Tensile Strength:	14.4	8 psi min
Elongation :	90	70% min
Tear Strength:	2.9	2.0 ilbs/ in min
CFD60%I:	0	N/A
50% Compression Set:	5.0	15% max
MVSS302 Flammability:		N/A
HF-1 ULH94 Flammability:		N/A
25%R IFD:	53	40-60 lbs
Permeability:		N/A

Country of Origin: The United States of America

Sincerely,

**Dwayne Rodgers D.R.**

Certification Tech: TS

Foam N' More Quality Assurance Lab

The exportation of this product is governed by U.S. regulations and is administered by the U.S. Department of Commerce. Diversion of this product contrary to U.S law is strictly prohibited. If you export or divert this product and require assistance in understanding these regulations, contact the U.S. Department of Commerce at 202-482-4811 or at [www.bis.doc.gov](http://www.bis.doc.gov).

Disclaimer: This certificate is being provided electronically as a matter of convenience to our customers. Tampering with this document is strictly prohibited. The original document on file in Foam N' More's offices located at Clawson, Michigan and is available upon request

ISO/TS 16949/ISO 14001/ISO 9001 Registered